



HULME MARTIN HEAT SEALERS

# HULME MARTIN HEAT SEALERS

[www.hulmemartin.co.uk](http://www.hulmemartin.co.uk)

Hulme Martin Heat Sealers Ltd  
Unit 5B, Country Business Centre,  
White Cottage Farm,  
Lucas Green Road,  
West End  
Woking  
Surrey  
GU24 9LZ  
Tel: (+44) 01483 476767  
Fax :(+44) 01483 486343

## **HM 1300 STD** **Medium Capacity** **Impulse Heat Sealers**

Maximum Sealing Length	340mm (13ins)
Seal Width	3mm standard
Film Thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240 Volts, 110 Volt conversion
Power Consumption	325 Watts per seal
Fuse Rating	T 3.15 Amp
Footprint	454mm (L) x 190mm (W) x 190mm (H)
Weight	10.7 Kgs
Operation	Foot operated via chain and pedal
Mounting	Bench mounted or optional Stand Kit
Options	Stand Kit, Rollers, Brackets and Retainers for layflat tubing, 6mm wide seal, T-wire for seal-cut-seal, Round wire for cut-and-seal



General-purpose foot operated machines providing great flexibility of operation. Leave hands free to manipulate large or heavy packages. Simple bench mounting or optional stand available. This standard model has a single electronic timer for control of the heating cycle only. This machine is simple to maintain with consumable spares being easy to fit and available from stock.