



HULME MARTIN HEAT SEALERS

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd
Unit 5B, Country Business Centre,
White Cottage Farm,
Lucas Green Road,
West End
Woking
Surrey
GU24 9LZ
Tel: (+44) 01483 476767
Fax :(+44) 01483 486343

HM 1800 D **Medium Capacity** **Impulse Heat Sealers**

Maximum Sealing Length	490mm (19.5ins)
Seal Width	3mm standard
Film Thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240 Volts, 110 Volt conversion
Power Consumption	415 Watts per seal
Fuse Rating	T 3.15 Amp
Footprint	607mm (L) x 190mm (W) x 190mm (H)
Weight	12.5 Kgs
Operation	Foot operated via chain and pedal
Mounting	Bench mounted or optional Stand Kit
Options	Stand Kit, Rollers, Brackets and Retainers for layflat tubing, 6mm wide seal, T-wire for seal-cut-seal, Round wire for cut-and-seal



General-purpose foot operated machines providing great flexibility of operation. Leave hands free to manipulate large or heavy packages. Simple bench mounting or optional stand available. This Duo model has a dual electronic timer for complete control of the heating and cooling cycle. This machine is simple to maintain with consumable spares being easy to fit and available from stock.