



HULME MARTIN HEAT SEALERS

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd
Unit 5B, Country Business Centre
White Cottage Farm
Lucas Green Road, West End
Woking, Surrey
GU24 9LZ
Tel: (+44) 01483 476767
Fax :(+44) 01483 486343
Email: sales@hulmemartin.co.uk

Vacuum Chamber Model No. VMS 153FH

General

The VMS 153FH is a stainless steel floor model Vacuum Chamber machine on lockable castors. This model is ideal if the unit needs to be moved around as it uses a standard 240V supply so can be wheeled in to position to be used. With the same high specification of the VMS 153 this model offers a host of standard specifications and many optional ones.

Specifications

- 10 digital programs
- Vacuum pump 21m³/hr
- Filler plates supplied
- Soft air
-

Options

Trim Seal
8mm Seal
2nd Seal Bar
Vacuum Sensor
Multi-Cycle
Gas Flush



Specifications of VMS 153	
Machine Size (LxWxH) mm	490 x 525 x 985
Chamber size (LxWxH) mm	420 x 420 x 180
Effective chamber size mm	410 x 370
Seal length mm	1 x 410
Seal width mm	3.5 parallel seal
Vacuum Pump	21m ³ /h
Consumption	0.75 – 1.0 kW
Power requirements	240 Volt 13 amp supply

VACUUM CHAMBER MACHINES

Operation

A vacuum chamber removes the air out of a bag by use of a vacuum pump. Once the air has been removed the bag is then sealed. The models start with a small tabletop model and progress through various sizes. The cabinet of every model is made of stainless steel, while the chamber is either constructed of stainless steel (VMS machines) or aluminium (VM machines). All models come with filler plates so that the working height inside the chamber can be adjusted for the product.

OPTIONS

Gas Flushing

Adding gas to the package is a way of extending the shelf life of the product. The product, and the space around it in the chamber are vacuumised as normal. Usually after the vacuuming process the bag is sealed; but with gas flushing the pouch is injected with a gas or gas mixture. When the desired volume of gas is reached the bag is then sealed. This gives a very low residual oxygen percentage and the product is no longer under vacuum pressure.

Soft Air

Soft-air is the ideal function to enable fragile (e.g. fish) or sharp (e.g. T-bone) products to be packed without damage. The air enters the vacuum chamber very gently after the sealing process giving the vacuum bag time to form around the fragile or sharp product. The result is that the product or the vacuum bag will not be damaged.

An additional benefit is that the product looks neater with a better formed package.

Sensor

When it is important to obtain an exact vacuum or gas level we recommend a sensor. The standard machine normally relies on a time cycle for the vacuum and gas levels, which is accurate enough for most applications. However, when dealing with products that vary in volume or density, a sensor ensures that each package is under the same level of vacuum.

Multi-cycles

Sometimes it may be necessary to have a repeated sequence of vacuuming and gassing. The multi-cycles option makes this possible with up to 8 processes in one cycle. All models (except VMS 43,53,113 and 133) can be equipped with the multi-cycle option. It is not possible to combine the multi-cycle with the sensor option