



HULME MARTIN HEAT SEALERS

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd
Unit 5B, Country Business Centre,
White Cottage Farm,
Lucas Green Road, West End,
Woking, Surrey,
GU24 9LZ
Tel: (+44) 01483 476767
Fax: (+44) 01483 486343
Email: sales@hulmemartin.co.uk



HM 2950 Stainless Steel

Specifically designed for food,
medical & laboratory applications

Perfect for:

- *Bakeries*
- *Hospitals*
- *Butchers*
- *Deli Counter*
- *Supermarkets*
- *Kitchens/Food Courts*



+ Comes with a FREE Heater Bar Assembly!

Maximum Sealing Length	310mm (12.5")
Seal Width	3mm ONLY
Film Thickness	2 x 1000 gauge (2 x 250 micron)
Voltage	240V, 110V (Conversion)
Power Consumption (Watts)	300W (per seal)
Fuse Rating	T 3.15 Amp
Footprint	374mm (L) x 161mm (W) x 190mm (H)
Weight	7.8kg
Operation	Hand Operated
Mounting	Bench Mounted
Body Construction	316 Stainless Steel

IMPULSE • CONSTANT HEAT SEALERS • VACUUM SEALERS • SHRINK CHAMBERS
SACK SEALERS • BESPOKE SOLUTIONS • SEMI-AUTOMATIC MACHINES • SECURITY SEALERS

Registered Office: Unit 5B Country Business Centre, White Cottage Farm, Lucas Green Road, West End, Woking, Surrey, GU24 9LZ
Registered in England No. 5484051 VAT No. GB 864 4792 82



HULME MARTIN HEAT SEALERS

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd
Unit 5B, Country Business Centre,
White Cottage Farm,
Lucas Green Road, West End,
Woking, Surrey,
GU24 9LZ
Tel: (+44) 01483 476767
Fax: (+44) 01483 486343
Email: sales@hulmemartin.co.uk

HM2950

Stainless Steel



Hand Operated

Impulse Heat Sealer

When hygiene, health & safety criteria require an easily cleaned, ***moisture resistant*** and non-corrosive sealer, then the **HM2950** will be ***perfect*** for your needs!

Constructed from food grade ***316 Stainless Steel***, with a low voltage safety operation and IP rated components.

This machine is used in many ***hospitals*** for packing medical samples,

& also can be found in many ***supermarkets*** in the fresh fish &

bakery sections. The sealing element is of the impulse type, so power is only

used during the sealing cycle of the machine, ***reducing running costs*** compared to constant heat models.

The sealing element uses low voltage for additional health & safety requirements when used around liquids.

It is simple to maintain, with consumable spares being easy to fit & ***available from stock***.

(for further information visit www.hulmemartin.co.uk)

IMPULSE • CONSTANT HEAT SEALERS • VACUUM SEALERS • SHRINK CHAMBERS
SACK SEALERS • BESPOKE SOLUTIONS • SEMI-AUTOMATIC MACHINES • SECURITY SEALERS

Registered Office: Unit 5B Country Business Centre, White Cottage Farm, Lucas Green Road, West End, Woking, Surrey, GU24 9LZ
Registered in England No. 5484051 VAT No. GB 864 4792 82