



HULME MARTIN HEAT SEALERS

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd
Unit 5B, Country Business Centre
White Cottage Farm
Lucas Green Road, West End
Woking, Surrey
GU24 9LZ
Tel: 01483 476767
Fax : 01483 486343
Email: info@hulmemartin.co.uk



HM 2500 —E/Standard—

(Hand Operated, Standard Impulse Heat Sealer) – Part No. 25001051

Maximum Sealing Length	240mm (9.5")
Seal Width	3mm (Standard)
Film Thickness	2 x 1000 gauge (4 x 250 micron)
Voltage	240V, 110V (Conversion)
Power Consumption (Watts)	165W (per seal)
Fuse Rating	T 3.15 amp
Footprint	338mm (L) x 123mm (W) x 170mm (H)
Weight	5.1 Kg
Operation	Hand Operated
Mounting	Bench or Wall Mounted
Options	T-Wire (Seal-Cut-Seal), Round Wire (Cut-&-Seal), Stand Kit, Rollers/Brackets & Retainers (for Layflat Tubing)

The **HM 2500 (E/Standard)** – Standard Impulse Heat Sealer

A general purpose bench or wall mounted Standard Impulse Sealer.

Instant seals without warm-up, but capable of high volume production work.

The parallel open ended sealing jaws allow occasional larger bags to be sealed by repositioning the bag along the element.

This machine is simple to maintain with consumable spares being easy to fit & available from stock.

**IMPULSE • CONSTANT HEAT SEALERS • VACUUM SEALERS • SHRINK CHAMBERS
SACK SEALERS • BESPOKE SOLUTIONS • SEMI-AUTOMATIC MACHINES • SECURITY SEALERS**
Registered office: Unit 5B Country Business Centre, White Cottage Farm, Lucas Green Road, West End, Woking, Surrey, GU24 9LZ
Registered in England No. 5484051 VAT No. GB 864 4792 82